

Appl. No. 10/682,413  
Amdt. dated 01/06/2006  
Reply to Office Action of 10/06/2005

**BEST AVAILABLE COPY**

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listing of claims, in the Application.

Listing of claims:

1. (Original) A method of servicing a plurality of read requests using a common mirror comprising the steps of:

determining whether the amount of data requested by the read requests is within a user-configurable threshold;

chaining the read requests together if the amount of data requested by the read requests is within the user-configurable threshold; and

sending the chained requests to the common mirror for servicing.

2. (Original) The method of Claim 1 wherein the common mirror is a least used mirror in a set of mirrors.
3. (Original) The method of Claim 2 wherein it is ascertained that the data being requested by the read requests is within a user-configurable range before chaining the read requests together.

AUS920030526US1

Appl. No. 10/682,413  
 Amdt. dated 01/06/2006  
 Reply to Office Action of 10/06/2005

4. (Original) The method of Claim 2 wherein it is ascertained that the plurality of read requests is to be grouped together before the read requests are chained together.
  
5. (Original) A method of servicing a read request using a common mirror comprising the steps of:  
  
 receiving a first read request;  
  
 sending the first read request to a mirror to be serviced;  
  
 receiving a second read request;  
  
 determining whether the amount of data requested by the first and the second read requests is within a user-configurable threshold; and  
  
 sending, if the amount of data requested by the first and the second read requests is within the user-configurable threshold, the read request to the mirror to which the first read request was sent to be serviced.
  
6. (Original) The method of Claim 5 further including the step of determining whether the first read request is presently being serviced when the second read request is received.

AUS920030526US1

Appl. No. 10/682,413  
Amdt. dated 01/06/2006  
Reply to Office Action of 10/06/2005

7. (Original) The method of Claim 6 wherein if the first read request is being serviced when the second read request is received, it is ascertained that the data being requested by the second read request is within a user-configurable range of the data requested by the first read request before the second read request is sent to the same mirror as the first read request.
8. (Original) The method of Claim 6 wherein if the first read request is not being serviced when the second read request is received, it is ascertained that the second read request is received within a user-configurable time frame from the first read request before the second read request is sent to the same mirror as the first read request.
9. (Currently amended) A computer program product on a computer readable medium for servicing a plurality of read requests using a common mirror comprising:  
  
instruction code ~~means~~ for determining whether the amount of data requested by the read requests is within a user-configurable threshold;  
  
instruction code ~~means~~ for chaining together the read requests if the amount of data requested by the read requests is within the user-configurable threshold;  
and

AUS920030526US1

Appl. No. 10/682,413

Amdt. dated 01/06/2006

Reply to Office Action of 10/06/2005

instruction code ~~means~~ for sending the chained requests to the common mirror for servicing.

10. (Original) The computer program product of Claim 9 wherein the common mirror is a least used mirror in a set of mirrors.

11. (Original) The computer program product of Claim 10 wherein it is ascertained that the data being requested by the read requests is within a user-configurable range before chaining the read requests together.

12. (Original) The computer program product of Claim 10 wherein it is ascertained that the plurality of read requests is to be grouped together before the read requests are chained together.

13. (Currently amended) A computer program product on a computer readable medium for servicing a read request using a common mirror comprising:

instruction code ~~means~~ for receiving a first read request;

instruction code ~~means~~ for sending the first read request to a mirror to be serviced;

instruction code ~~means~~ for receiving a second read request;

AUS920030526US1

Appl. No. 10/682,413  
Amdt. dated 01/06/2006  
Reply to Office Action of 10/06/2005

instruction code ~~means~~ for determining whether the amount of data requested by the first and the second read requests is within a user-configurable threshold; and

instruction code ~~means~~ for sending, if the amount of data requested by the first and the second read requests is within the user-configurable threshold, the read request to the mirror to which the first read request was sent to be serviced.

14. (Currently amended) The computer program product of claim 13 further comprising instruction code ~~means~~ for determining whether the first read request is presently being serviced when the second read request is received.
15. (Original) The computer program product of claim 14 wherein if the first read request is being serviced when the second read request is received, it is ascertained that the data being requested by the second read request is within a user-configurable range of the data requested by the first read request before the second read request is sent to the same mirror as the first read request.
16. (Original) The computer program product of claim 14 wherein if the first read request is not being serviced when the second read request is received, it

AUS920030526US1

Appl. No. 10/682,413

Amdt. dated 01/06/2006

Reply to Office Action of 10/06/2005

is ascertained that the second read request is received within a user-configurable time frame from the first read request before the second read request is sent to the same mirror as the first read request.

17. (Original) A system for servicing a plurality of read requests using a common mirror comprising:

at least one storage device for storing code data; and

at least one processor for processing the code data to determine whether the amount of data requested by the read requests is within a user-configurable threshold, to chain together the read requests if the amount of data requested by the read requests is within the user-configurable threshold, and to send the chained requests to the common mirror for servicing.

18. (Original) The system of Claim 17 wherein the common mirror is a least used mirror in a set of mirrors.

19. (Original) The system of Claim 18 wherein it is ascertained that the data being requested by the read requests is within a user-configurable range before chaining the read requests together.

20. (Original) The system of Claim 18 wherein it is ascertained that the plurality of read requests is to be grouped together before the read requests are chained together.

AUS920030526US1

Appl. No. 10/682,413  
Amdt. dated 01/06/2006  
Reply to Office Action of 10/06/2005

21. (Original) A system for servicing a read request using a common mirror comprising:

at least one storage device for storing code data; and

at least one processor for processing the code data to receive a first read request, to send the first read request to a mirror to be serviced, to receive a second read request, to determine whether the amount of data requested by the first and the second read requests is within a user-configurable threshold, and to send, if the amount of data requested by the first and the second read requests is within the user-configurable threshold, the read request to the mirror to which the first read request was sent to be serviced.

22. (Original) The system of Claim 21 further processing the code data to determine whether the first read request is presently being serviced when the second read request is received.

23. (Original) The system of Claim 22 wherein if the first read request is being serviced when the second read request is received, it is ascertained that the data being requested by the second read request is within a user-configurable range of the data requested by the first read request before the second read request is sent to the same mirror as the first read request.

AUS920030526US1

Appl. No. 10/682,413  
Amdt. dated 01/06/2006  
Reply to Office Action of 10/06/2005

24. (Original) The system of Claim 22 wherein if the first read request is not being serviced when the second read request is received, it is ascertained that the second read request is received within a user-configurable time frame from the first read request before the second read request is sent to the same mirror as the first read request.

AUS920030526US1



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**